

Date: Thursday, 02/10/2008 10:34:38 AM
 User: Julie Lecocq

Process Sheet

Customer : CU-DAR001 Dart Helicopters Services	Drawing Name : BLADE FITTING
Job Number : 42415	
Estimate Number : 12300	
P.O. Number :	Part Number : D3488042
This Issue : 02/10/2008 S.O. No. :	Drawing Number : D3488 / DSK101
Prsht Rev. : NC	Project Number : N/A
First Issue : / / Type : MACHINED PARTS	Drawing Revision : B / D
Previous Run : 41206	Material :
Written By :	Due Date : 10/10/2008 Qty: 20 Um: Each
Checked & Approved By : <u>JLD 08.10.02</u>	
Comment : Est Rev:A New Issue 06-02-28 JLM	
Est Rev:B As per Rev B 06-03-30 JLM	
Est Rev:C Now On Doosan Lathe JLM Verified BY:DD	

Additional Product

Job Number:



Seq. #:	Machine Or Operation:	Description :
---------	-----------------------	---------------

1.0	D6103003	Round Billet, Aluminum
-----	----------	------------------------



Comment: Qty.: 1.0000 Each(s)/Unit Total : 20.0000 Each(s)

Alluminum Round Billet D6103-003

Batch: B 41965 X 16 pcs

B 41609 X 4 pcs

J.F. 08/10/10 (20)

2.0	DOOSAN LATHE	DOOSAN LATHE
-----	--------------	--------------



(P12)

Comment: DOOSAN CNC LATHE

1-Turn as per Dwg DSK 101 & Folio FA627

2-Deburr

J.F. 08/10/10 (20)

3.0	QC2	INSPECT PARTS AS THEY COME OFF MACHINE
-----	-----	--



Comment: INSPECT PARTS AS THEY COME OFF MACHINE

J.F. 08/10/10 (20)

4.0	HAAS1	HAAS CNC VERTICAL MACHINING #1
-----	-------	--------------------------------



Comment: HAAS CNC VERTICAL MACHINING #1

1-Machine as per Folio FA627 & Dwg D3488

2-Deburr

J.L. 08/10/10 (20)

W/O:		WORK ORDER CHANGES					
DATE	STEP	PROCEDURE CHANGE	By	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector

Part No: D3488-042 PAR #: _____ Fault Category: _____ NCR: Yes (No) DQA: D Date: 08/10/09
 Resolution: _____ Disposition: _____ QA: N/C Closed: _____ Date: _____

NCR: <u>42415</u>		WORK ORDER NON-CONFORMANCE (NCR)						
DATE	STEP	Description of NC Section A	Corrective Action Section B			Verification Section C	Approval Chief Eng	Approval QC Inspector
			Initial Chief Eng	Action Description Chief Eng	Sign & Date			
8/10/09	# 20	During machining it was found that chatter was on inside of Bore. During removal of the chatter the B	PH QSI 042 08.10.09	Acceptable deviation - see attached analysis	PH QSI 042 08.10.09	50/10/09	PH QSI 042 08.10.09	50/10/09
		2.150" Bore was machined to 2.175" .025 over nominal. EC chatter on inside from Boring			JF 08/10/09			

NOTE: Date & initial all entries

Date: Thursday, 02/10/2008 10:34:38 AM
User: Julie Lecocq

Process Sheet

Customer: CU-DAR001 Dart Helicopters Services

Drawing Name: BLADE FITTING

Job Number: 42415

Part Number: D3488042

Job Number:



Seq. #:

Machine Or Operation:

Description :

5.0

QC2

INSPECT PARTS AS THEY COME OFF MACHINE



Comment: INSPECT PARTS AS THEY COME OFF MACHINE

J.L 08/10/18

6.0

QC8

SECOND CHECK



Comment: SECOND CHECK

SL 08/10/19

7.0

HAND FINISHING1

HAND FINISHING RESOURCE #1



Comment: HAND FINISHING RESOURCE #1

Chemical Conversion Coat as per QSI 005 4.1

M-L

08/10/20

8.0

POWDER COATING

POWDER COATING



Comment: POWDER COATING

Powder Coat White Gloss (Ref: 4.3.5.1) as per QSI 005 4.3

START TIME:

OVEN TEMPERATURE:

FINISH TIME:

11:25
320 °F
11:55

M-L

08/10/20

9.0

QC3

INSPECT POWDER COAT/CHEMICAL CONVERSION



Comment: INSPECT POWDER COAT/CHEMICAL CONVERSION

FL 08/10/20

(20)

10.0

ALS71032225

INSERT



Comment: Qty.: 4.0000 Each(s)/Unit Total: 80.0000 Each(s)

Pick:

Qty Part Number Description Batch

4 ALS7-1032-225 Insert

M/00621

FL

11.0

HAND FINISHING1

HAND FINISHING RESOURCE #1



Comment: HAND FINISHING RESOURCE #1

Install Inserts as per Dwg D3488

FL 08/10/20

(20)

W/O:		WORK ORDER CHANGES					
DATE	STEP	PROCEDURE CHANGE	By	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector

Part No: _____ PAR #: _____ Fault Category: _____ NCR: Yes No DQA: _____ Date: _____

Resolution: _____ Disposition: _____ QA: N/C Closed: _____ Date: _____

NCR:		WORK ORDER NON-CONFORMANCE (NCR)						
DATE	STEP	Description of NC Section A	Corrective Action Section B			Verification Section C	Approval Chief Eng	Approval QC Inspector
			Initial Chief Eng	Action Description Chief Eng	Sign & Date			

NOTE: Date & initial all entries

Date: Thursday, 02/10/2008 10:34:39 AM
User: Julie Lecocq

Process Sheet

Customer: CU-DAR001 Dart Helicopters Services

Drawing Name: BLADE FITTING

Job Number: 42415

Part Number: D3488042

Job Number:



Seq. #:	Machine Or Operation:	Description :
---------	-----------------------	---------------

12.0

QC5

INSPECT WORK TO CURRENT STEP



countes

Comment: INSPECT WORK TO CURRENT STEP

08/10/20 (20)

13.0

PACKAGING 1

PACKAGING RESOURCE #1



Comment: PACKAGING RESOURCE #1

Identify and Stock

Location: *FL-8*

FZ 08/10/20 (20)

14.0

QC21

FINAL INSPECTION/W/O RELEASE



Comment: FINAL INSPECTION/W/O RELEASE

08/10/21 FZ

Job Completion



CMF 08-10-20

W/O:		WORK ORDER CHANGES					
DATE	STEP	PROCEDURE CHANGE	By	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector

Part No: _____ PAR #: _____ Fault Category: _____ NCR: Yes No DQA: _____ Date: _____

Resolution: _____ Disposition: _____ QA: N/C Closed: _____ Date: _____

NCR:		WORK ORDER NON-CONFORMANCE (NCR)						
DATE	STEP	Description of NC Section A	Corrective Action Section B			Verification Section C	Approval Chief Eng	Approval QC Inspector
			Initial Chief Eng	Action Description Chief Eng	Sign & Date			

NOTE: Date & initial all entries

DART AEROSPACE LTD		Work Order: 42415
Description: Blade Fitting, RH		Part Number: D3488-2
Inspection Dwg: D3488	Rev: B	Page 1 of 1


FIRST ARTICLE INSPECTION CHECKLIST

☒ First Article ☐ Prototype

Drawing Dimension	Tolerance	Actual Dimension	Accept	Reject	Method of Inspection	Comments
0.125	+/-0.010	.131"	✓			
2.620	+/-0.010	2.617"	✓			
0.793	+/-0.010	.803	✓			
1.351	+/-0.010	1.348	✓			
1.317	+/-0.010	1.311	✓			
90°	+/-0.1°	90°	✓			
1.802	+/-0.010	1.812	✓			
Ø0.508	+0.006/-0.001	.508	✓			
R0.062	+/-0.010	.062	✓			
1.500	+/-0.010	1.498	✓			
8.000	+0.030/-0.000	8.003"	✓			
11.18	+/-0.030	11.180	✓			
Ø0.484	+0.005/-0.001	Ø.486"	✓			
1.180	+/-0.010	1.181"	✓			
3.150	+/-0.010	3.152"	✓			
3.070	+/-0.010	3.067"	✓			
0.590	+/-0.010	.591	✓			
0.125	+/-0.010	.130	✓			
1.005	+/-0.010	1.005"	✓			
3.500	+/-0.010	3.500"	✓			
Ø0.297	+0.005/-0.000	Ø.301"	✓			
Ø0.430	+/-0.010	Ø.432"	✓			
0.100	+/-0.010	.102"	✓			

Measured by: J.F./J.L.	Audited by: S.B.	Prototype Approval:	N/A
Date: 08/10/10	Date: 08/10/19	Date:	N/A


Rev	Date	Change	Revised by	Approved
A	06.03.31	New Issue	KJ/JLM	[Signature]



SECTION B-B

0.297
C'BORE 0.430 x 0.100
INSTALL ALS4-1032-225 (OR AKS4-1032-225
OR ALS7-1032-225 OR AKS7-1032-225)
INSERTS AFTER FINISH
(4 PLACES)

4



SECTION A-A


D3488-041/-042 BLADE FITTING ASSEMBLY PARTS LIST

QTY -041	QTY -042	PART NUMBER	DESCRIPTION
X	X	D3488-041	BLADE FITTING ASSEMBLY (LH)
		D3488-042	BLADE FITTING ASSEMBLY (RH)
1		D3488-1	BLADE FITTING (LH)
	1	D3488-2	BLADE FITTING (RH)
4	4	ALS4-1032-225 or AKS4-1032-225 or ALS7-1032-225 or AKS7-1032-225	INSERT



D3488-041/-042 BLADE FITTING

- MATERIAL: MAKE D3488-1/-2 FROM ALUMINUM 7075-T7351 ROUND BAR
PER QQ-A-225/9
(REF. DART MATERIAL SPEC M7075T73R)
- FINISH: ACID ETCH, ALODINE PER DART QSI 005 4.1
POWDER COAT WHITE (REF 4.3.5.1) PER DART QSI 005
- BREAK UNMARKED SHARP EDGES 0.010 TO 0.020
- INSTALL INSERTS AFTER POWDER COAT
- ALL DIMENSIONS ARE IN INCHES
- TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED

NO WORK ORDER
RETURN TO
ENGINEERING
UNCONTROLLED COPY
SUBJECT TO AMENDMENT
WITHOUT NOTICE



DETAIL C



D3488-041 SHOWN (D3488-042 OPPOSITE)


RELEASED
06.03.15
PER DS
ECN #739

B	06.03.15	CHANGE THICKNESS
A	05.12.20	NEW ISSUE
DESIGN	PH	DART DART AEROSPACE USA, INC. PORT HADLOCK, WA
CHECKED	PH	DART DART AEROSPACE USA, INC. PORT HADLOCK, WA
DATE	06.03.15	BLADE FITTING
DRAWING NO.	D3488	REV. B
TITLE	BLADE FITTING	SHEET 1 OF 1
SCALE	1:3	

COPYRIGHT © 2005 BY DART AEROSPACE USA, INC.
THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL
AND IS SUPPLIED ON THE EXPRESS CONDITION
THAT IT IS NOT TO BE USED FOR ANY PURPOSE
OR COPIED OR COMMUNICATED TO ANY OTHER
PERSON WITHOUT WRITTEN PERMISSION FROM
DART AEROSPACE USA, INC.

DART

DESIGN	DRAWN BY	DART AEROSPACE USA, INC.	
04	04	PORT HADLOCK, WA	
CHECKED	APPROVED	DRAWING NO.	REV. D
<i>[Signature]</i>	<i>[Signature]</i>	DSK 101	SHEET 1 OF 1
DATE		TITLE	SCALE
06.05.09		D3488-1/-2 TURNING DETAIL	1:3
A	05.12.21	NEW ISSUE	
B	06.03.02	ADD TOLERANCES AND RADIUS	
C	06.04.17	0.188 WAS 0.125	
D	06.05.09	REMOVE DIAMETER FOR CHAMFER	



DSK 101

- 1) MATERIAL: MAKE FROM ALUMINUM 7075-T7351 ROUND BAR PER QQ-A-225/9 (REF. DART MATERIAL SPEC M7075T73R)
- 2) FINISH: NONE
- 3) BREAK UNMARKED SHARP EDGES 0.010 TO 0.020
- 4) ALL DIMENSIONS ARE IN INCHES
- 5) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED

Deviation for 03418-042 B42415
 $\phi 2.175$ instead of $\phi 2.150$ *08-10-09*

For installation of the Apical Tri-bag and Apical Cylindrical Float bag systems onto OEM skid tubes; it is required that the OEM P/N 350A41-1077-24/-25 blade fitting be substituted with the Apical P/N 20473-7/-8 blade fitting. In the proposed Dart skid tube configuration, the Dart D3488-041/-042 blade fitting will replace the Apical P/N 20473-7/-8 blade fitting.

In the Dart system, blade fitting D3488-041/-042 will be used to transfer load into the web of the skid tube assembly. On the outside of the skid tube, D3488-041/-042 is dimensionally identical to the Apical P/N 20473-7/-8 blade fitting and is manufactured from the same 7075-T7351 material. Therefore, the Dart blade fitting and the Apical blade fitting have identical structural capability. The longitudinal location of the holes on the D3488-041/-042 blade fitting used to mount the aft crosstube are identical to the Apical P/N 20473-7/-8 blade fitting. On the inside of the skid tube, D3488-041/-042 has been designed to withstand higher bending moments than the Apical fitting.

The following table compares the Dart D3488-041/-042 blade fitting to the Apical 20473-7/-8 blade fitting.

Component	Dart D3488-041/-042	Apical P/N 20473-7/-8
Material	7075-T7351 per QQ-A-225/9	7075-T7351 per QQ-A-225/9
(I) Moment of Inertia of portion inside skid tube	1.620 in ⁴ (from D3488-041/-042 dwg)	1.567 in ⁴ (from D20473-7/-8 dwg)
(C) Distance to outer fibers	1.310 in (from D3488-041/-042 dwg)	1.445 in (from 20473-7/-8 dwg)
(A) Area at section A-A	2.280 in ²	1.792 in ²
Z=I/C at section A-A	1.234 in ³	1.084 in ³
D	10.69 in	10.53 in

w/
deviation

1.573



1.310

2.199


1.201

N/C

ϕ
 Dart is still greater I, C, A, I/C, D
 - acceptable deviation



SECTION A-A
 APICAL P/N
 20473-7/-8
 BLADE FITTING



SECTION A-A
 DART P/N
 D3488-041/-042
 BLADE FITTING

Wb 42415